

## MATERIAL SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH)

## AIRSEAL 2 & 2 Tacky

#### **1 - IDENTIFICATION OF THE PREPARATION AND THE COMPANY/BUSINESS**

## Identification of the substance or preparation

Name of product:

Article:

**AIRSEAL 2 & 2 Tacky** 

## Use of the substance / preparation

Vacuum bag sealant tape

Company / undertaking identification		
Company name:	AIRTECH INTERNATIONAL	
Street/POB No.:	5700 Skylab Road	
State/city/postal code:	Huntington Beach CA 92647	
Telephone:	714-899-8100	
Fax:	714-899-8179	
Dept./responsible for information:		
Emergency telephone	800-424-9300	

**2 - HAZARDS IDENTIFICATION** 

## **Classification:** Article

According to EC directives or the corresponding national regulations there is no labeling obligation for this product.

## **3 – COMPOSITION/INFORMATION ON INGREDIENTS**

Product class: Butyl based extruded tape

## 4 - FIRST AID MEASURES

Skin contact: Wash with soap and water. Seek medical advice if irritation persists.

Inhalation: Not a probable route of exposure. In case of accidental inhalation of fumes from overheating or when involved in a fire, move to fresh air. Consult a physician after significant exposure.

Eve contact: Immediately flush with plenty of water for 15 minutes. Seek medical advice if irritation persists.

Ingestion: Not a probable route of exposure.

## 5 - FIRE-FIGHTING MEASURES

Suitable extinguishing media: Water fog, carbon dioxide, foam, dry chemical.

Extinguishing media which must not be used for safety reasons: High power water jet.

Special exposure hazards arising from the substance or preparation itself, combustion products: In case of thermal decomposition, carbon monoxide, carbon dioxide and other toxic gases or fumes are evolved.

Special protective equipment: Normal firefighting procedures should be followed to avoid inhalation of smoke and gases. Firefighters should wear full protective clothing including self contained breathing apparatus.

#### **6 - ACCIDENTAL RELEASE MEASURES**

Environmental precautions: Do not allow to enter ground water, sewage or drains.

Cleaning methods: This material is a solid, it will not spill. Collect the product and store into containers for disposal.

#### 7 - HANDLING AND STORAGE

Handling: No special measures.

Storage: Store in a cool, dry place at 20-25°C. Do not freeze.

## 8 - EXPOSURE CONTROLS/ PERSONAL PROTECTION



# **MATERIAL SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH)

AIRSEAL 2 & 2 Tacky

#### Exposure limit values: None

**Exposure controls:** Overall room ventilation and/or local exhaust at points of fume generation in the work area.

#### Occupational exposure controls:

Respiratory protection:	None under normal usage.
Hand protection:	Protective gloves according to EN 407 are required when handling hot material.
Eye protection:	Not a probable route of exposure. Use safety glasses according to EN 166 as a good general safety practice.
Hygiene measures:	Wash hands before handling food and at the end of work.

#### 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Soft, tacky black strip, extruded on release paper.
Odor:	Very low.
pH:	Not applicable
Solubility in water:	Insoluble.
Flash point:	Not applicable.
Volatile content:	Very low.
Melting point/range:	Not applicable
Boiling point:	Not applicable
Specific gravity:	1.4- 1.6

## **10 - STABILITY AND REACTIVITY**

**Conditions to avoid:** Heating above maximum use temperature.

Materials to avoid: Strong oxidizing agents.

Hazardous decomposition products: Decomposition products generated in case of fire are carbon monoxide, carbon dioxide and irritating smoke.

Additional information: The product is stable at the handling and storage conditions recommended per § 7 of the safety data sheet and under normal processing conditions.

#### 11 - TOXICOLOGICAL INFORMATION

No known adverse health effects.

## **12 - ECOLOGICAL INFORMATION**

#### Ecotoxicity:

Water hazard class: 1 = mild water pollutant

#### Persistence and degradability:

Product is not biodegradable.

#### Additional ecological information:

Do not allow to enter ground water, sewage or drains.

#### **13 - DISPOSAL CONSIDERATIONS**



# **MATERIAL SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH)

## AIRSEAL 2 & 2 Tacky

**Disposal recommendations:** Disposal of the product and the packaging must be done in compliance with local, state and federal regulations.

Product: European waste key numbers: 070213 = Plastic waste

**Contaminated packaging:** Waste key number 150101 – Paper and cardboard packaging.

Waste key number 150102 - Plastic packaging.

## **14 - TRANSPORT INFORMATION**

Not classified as hazardous under transport regulations (ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport).

## **15 - REGULATORY INFORMATION**

This product was classified in compliance with the directive known as <All preparations> 88/379/EEC and its adaptations. The product as shipped is not subject to labeling according to EC directives.

## **16 - OTHER INFORMATION**

This bulletin cannot cover all possible situations which the user may experience during processing. Each aspect of your operation should be examines to determine if, or where, additional precautions may be necessary. All health and safety information contained in this bulletin should be provided to your employees or customers. It is your responsibility to use this information to develop appropriate work practice guidelines and employee instructional programs for your operation.

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of this material. The information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations but all statements or suggestions are made without warranty, express or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.

Revision: Addition of the Airseal 2 Tacky version