# MATERIAL SAFETY DATA SHEET

# D3707 HULL-GARD EPOXY PRIMER CONVERTER

MSDS Revision No: E: MSDS Revision Date: 08

**EMERGENCY NUMBERS:** 

E2 -0 08/24/2004

Akzo Nobel Coatings

Awlgrip North America

(703) 527-3887

**CUSTOMER SERVICE:** 

CHEMTREC (USA)
CHEMTREC (Intl)

Sales Order: {SalesOrd}

2270 Morris Avenue

(800) 854-6813

(800) 424-9300

Poison Control Center

P. O. Box 386

(888) 355-3090

(Non-Emergency)

AWLGRIP (Phone)

Union, NJ 07083

(908) 686-1752

AWLGRIP (Fax)

# 1. GENERAL INFORMATION

Product Identity: D3707 HULL-GARD EPOXY PRIMER CONVERTER

Bulk Sales Reference No: OD3707

**IMPORTANT:** Read this MSDS before handling or disposing of this product, and provide this information to the employee, customers, and users of this product. PLEASE NOTE THE MSDS REVISION NUMBER AT THE TOP OF THIS PAGE. If the MSDS Revision Number posted at the top of this page does not match the MSDS Revision Number on the product label, please contact Customer Service at the phone number included above for the correct MSDS. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard.

**NOTICE:** OSHA hazardous chemicals are listed in Section 2 if present at 1% or more. Carcinogens and extraordinarily/special hazardous chemicals are listed in Section 2 if present at .1% or more. Additional regulatory information for specific chemical categories is included in Section 15.

# 2. HAZARDOUS INGREDIENT INFORMATION

n-Butyl alcohol 25 - 50% by Weight	Source	Exposure Data	
		OSHA:	100 ppm TWA; 300 mg/m3 TWA50 ppm Ceiling; 150 mg/m3 Ceiling
		ACGIH:	20 ppm TWA
		NIOSH:	50 ppm Ceiling; 150 mg/m3 Ceiling1400 ppm IDLH
		Supplier:	No Data Available
		OHSA, CAN:	: 50 ppm CEV; 150 mg/m3 CEV
		Mexico:	50 ppm STEL; 150 mg/m3 STEL
		Brazil:	No Data Available
		Source	Health Data
		NIOSH:	Eye and mucous membrane irritation CNS depression
		Source	Carcinogen Data
		OSHA:	Select Carcinogen: No
		NTP:	Known Carcinogen: No; Suspected Carcinogen: No
		IARC:	Group 1: No; Group 2A: No; Group 2b: No; Group 3: No; Group 4: No

CAS No. 000100-41-4	Ingredient Name & %	Source	Exposure Data	
		OSHA:	100 ppm TWA; 435 mg/m3 TWA125 ppm STEL; 545 mg/m3 STEL	
		ACGIH:	100 ppm TWA125 ppm STEL 100 ppm TWA; 435 mg/m3 TWA125 ppm STEL; 545 mg/m3	
	Ethyl benzene 1.0 - 10% by Weight	NIOSH:	STEL800 ppm IDLH	
		Supplier:	No Data Available 100 ppm TWAEV; 435 mg/m3 TWAEV125 ppm STEV; 540 mg/n STEV	
		OHSA, CAN:		
		Mexico:	100 ppm TWA; 435 mg/m3 TWA125 ppm STEL; 545 mg/m3 STEL	
		Brazil:	78 ppm TWA; 340 mg/m3 TWA	
		Source	Health Data	
		NIOSH:	Eye skin	
		Source	Carcinogen Data	
		OSHA:	Select Carcinogen: No	
		NTP:	Known Carcinogen: No; Suspected Carcinogen: No	
		IARC:	Group 1: No; Group 2A: No; Group 2b: Yes; Group 3: No; Group 4: No	
			5.54p 25. 100, 5.64p 5.110, 5.64p 7.110	
CAS No.	Ingredient Name & %	Source	Exposure Data	
		OSHA:	No Data Available	
		ACGIH:	No Data Available	
		NIOSH:	No Data Available	
		Supplier:	No Data Available	
		OHSA, CAN:	: 0.5 ppm TWAEV; 3 mg/m3 TWAEV	
		Mexico:	No Data Available	
000112-24-3	Triethylene tetramine	Brazil:	No Data Available	
	1.0 - 10% by Weight	Source	Health Data	
		NIOSH:	No Data Available	
		Source	Carcinogen Data	
		OSHA:	Select Carcinogen: No	
		NTP:	Known Carcinogen: No; Suspected Carcinogen: No	
		IARC:	Group 1: No; Group 2A: No;	
			Group 2b: No; Group 3: No; Group 4: No	
CAS No.	Ingredient Name & %	Source	Exposure Data	
		OSHA:	100 ppm TWA; 435 mg/m3 TWA150 ppm STEL; 655 mg/m3 STEL	
		ACGIH:	100 ppm TWA150 ppm STEL	
		NIOSH:	No Data Available	
		Supplier:	No Data Available	
		OHSA, CAN:	100 ppm TWAEV; 435 mg/m3 TWAEV150 ppm STEV; 650 mg/m3 STEV	
		Mexico:	100 ppm TWA; 435 mg/m3 TWA150 ppm STEL; 655 mg/m3 STEL	
01330-20-7	Xylenes (o-, m-, p- isomers)	Brazil:	78 ppm TWA; 340 mg/m3 TWA	
	25 - 50% by Weight	Source	Health Data	
		NIOSH:	Central nervous system depressant; respiratory and eye irritation	

OSHA: Select Carcinogen: No

NTP: Known Carcinogen: No; Suspected Carcinogen: No

Group 1: No; Group 2A: No; IARC: Group 2b: No;

Group 4: No Group 3: Yes;

### HAZARD IDENTIFICATION 3.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent Overview:

brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may

be harmful or fatal. Avoid contact with eyes, skin and clothing.

Harmful if inhaled. Causes lung irritation. Causes nose and throat irritation. Vapors may affect the brain or nervous Inhalation:

system causing dizziness, headache or nausea.

Causes eye burns. Do not get in eyes. Eyes:

Causes skin burns. May be harmful if absorbed through the skin. Skin:

Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness. Ingestion:

Contains an ingredient which can cause organ damage (See Section 2 and Section 15 for each ingredient). **Chronic Effects:** 

**HMIS Rating:** Health: Unknown Flammability: Unknown Reactivity: Unknown

# FIRST AID MEASURES

Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. General:

Thoroughly clean or destroy contaminated shoes.

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get Inhalation:

medical attention immediately.

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention Eyes:

immediately.

In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately. Skin:

If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless Ingestion: instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.

# PROTECTIVE EQUIPMENT AND CONTROL MEASURES 5.

Select equipment to provide protection from the ingredients listed in Section 2 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring

demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M

does not endorse the accuracy of the information contained in this Material Safety Data Sheet.

Do not get in eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 2 of this document. Depending on the site-specific conditions of use, safety glasses, chemical

goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly

cleaned, or discarded after each use.

Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 2 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face Skin/Hand:

protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after

Respiratory:

Eyes:

Engineering Controls: Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential

Other Work Practices: exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of

soap and water.

FIRE AND EXPLOSION INFORMATION 6.

Flash Point: F: 80

Fire and Explosion Hazards:

Fire Fighting Procedures:

C: 27

Lower Explosive Limit (LEL): 1 (%vol in air) at Normal Atmospheric Temp and Pressure

> Flammable liquid and vapor. FLAMMABLE/COMBUSTIBLE MATERIALS: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or

confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Runoff to sewers may

create fire or explosion hazard. Containers may explode when heated.

CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient. SMALL FIRES: Use dry chemical, CO2, water spray or alcohol-resistant foam. LARGE FIRES: Use water spray, fog, or alcohol-resistant foam. Do not use straight streams. Move containers from fire area if you can do so without risk. Runoff from fire control may cause pollution. Dike fire control water for

later disposal. Do not scatter the material.

Also Reference Emergency Response Guide Number: 127

# 7. PHYSICAL AND CHEMICAL PROPERTIES

**Physical State:** Liquid

Not Determined :Ha

0.875804 **Specific Gravity:** 

243 **Boiling Point (F):** 

Vapor Density: Heavier than air

**VOC Content (lbs):** Refer to the Technical Data Sheet for this product.

Slower than ether **Evaporation Rate:** 

### 8. STABILITY AND REACTIVITY DATA

This product is stable and hazardous polymerization will not occur. General:

Strong oxidizing agents. **Incompatible Materials:** 

**Hazardous** May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon

Dioxide and Carbon Monoxide. **Decompostion:** 

## 9. HANDLING AND STORAGE

Store between 32 and 120 F **Storage Temperature:** 

Handling and Storage **Precautions:** 

General:

Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Vapors may cause flash fire or ignite explosively. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Do not get in eyes, on skin or clothing. Close container after each use. Wash thoroughly after handling.

### 10. **TOXICOLOGICAL DATA**

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Section 2 for

chemical specific data.

Page4 of 6

### 11. **ECOLOGICAL DATA**

No additional information provided for this product. See Section 2 for chemical specific data. General:

### 12. **ACCIDENTAL RELEASE MEASURES**

**Spill Response Procedures:** 

**Public Safety:** 

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed

material.

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind

evacuation for at least 300 meters (1000 feet).

Also, Reference Emergency Response Guide Number: 127

## **DISPOSAL CONSIDERATION** 13.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Waste Disposal: Section 15 if listed).

## TRANSPORTATION INFORMATION 14.

DOT (Domestic	Surface Transportation)	IMO / IMDG (Ocean Transportation)		
<b>DOT Proper Shipping Name:</b> PAINT		IMDG Proper Shipping Name: PAINT		
DOT Hazard Class:	3	IMDG Hazard Class:	3.3 - High flashpoint flammable liquids	
UN / NA Number:	UN 1263	UN Number:	UN 1263	
DOT Packing Group:	III	IMDG Packing Group:	III	
CERCLA/DOT RQ:	46 gal. / 338 lbs.	System Reference Code:	28	

### 15. REGULATORY INFORMATION

Regulatory Overview:	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.  Note: Any chemical ingredients listed in Section 15, that do not also appear in Section 2, are contained in the product at a concentration below the applicable OSHA threshold level of 1% or 0.1%.
	01 0.1%.

WHMIS Classification: Not Determined

**Regulatory List Product Ingredients on List** 

**DOT Marine Pollutants (10%):** 

(No Product Ingredients Listed) **DOT Severe Marine Pollutants (1%):** (No Product Ingredients Listed) EPCRA 311/312 Chemicals and RQs

(>.1%):

000100-41-4 Ethyl benzene: 1000 lb final RQ; 454 kg final RQ 000071-36-3 n-Butyl alcohol: 5000 lb final RQ; 2270 kg final RQ

001330-20-7 Xylenes (o-, m-, p- isomers): 100 lb final RQ; 45.4 kg final RQ

EPCRA 302 Extremely Hazardous (>.1%)

(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%): 000100-41-4 Ethyl benzene 000071-36-3 n-Butyl alcohol 001330-20-7 Xylenes (o-, m-, p- isomers) Mass RTK Substances (>1%): 000100-41-4 Ethyl benzene 000071-36-3 n-Butyl alcohol 000112-24-3 Triethylene tetramine 001330-20-7 Xylenes (o-, m-, p- isomers) Mass Extraordinarily Haz Sub (>.01%): (No Product Ingredients Listed) Penn RTK Substances (>1%): 000100-41-4 Ethyl benzene 000071-36-3 n-Butyl alcohol 000112-24-3 Triethylene tetramine 001330-20-7 Xylenes (o-, m-, p- isomers) **Penn Special Hazardous Substances** (>.01%): (No Product Ingredients Listed) **Rhode Island Hazardous Substances** (>.1%): 000100-41-4 Ethyl benzene 000071-36-3 n-Butyl alcohol 001330-20-7 Xylenes (o-, m-, p- isomers) RCRA Status (>.01%): (No Product Ingredients Listed) N.J. RTK Substances (>1%): 000100-41-4 Ethyl benzene 000071-36-3 n-Butyl alcohol 000112-24-3 Triethylene tetramine 001330-20-7 Xylenes (o-, m-, p- isomers) N.J. Special Hazardous Substances (>.01%): 000100-41-4 Ethyl benzene 000071-36-3 n-Butyl alcohol 000112-24-3 Triethylene tetramine 001330-20-7 Xylenes (o-, m-, p- isomers) N.J. Env. Hazardous Substances (>.1%): 000100-41-4 Ethyl benzene 000071-36-3 n-Butyl alcohol 001330-20-7 Xylenes (o-, m-, p- isomers) Proposition 65 - Carcinogens (>0%): (No Product Ingredients Listed) **Proposition 65 - Female Repro Toxins** (>0%): (No Product Ingredients Listed) **Proposition 65 - Male Repro Toxins** (>0%): (No Product Ingredients Listed) **Proposition 65 - Developmental Toxins** 

# 16. OTHER INFORMATION

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

# **End Of Document**

(No Product Ingredients Listed)

(>0%):